



# #120 FIBERED ALUMINUM ROOF COATING

**TROPICAL ROOFING PRODUCTS' #120 FIBERED ALUMINUM ROOF COATING** is a heavy-duty fibered aluminum coating that gives maximum reflectivity while giving unsurpassed protection against moisture and corrosion. Our unique formulation forms a heavy, brilliant, silvery finish that preserves, prevents rust, inhibits fungus, and reflects over 70% of the sun's damaging rays, while reducing interior temperatures. Our use of paint grade aluminum pigment ( as opposed to the coarser, less leafing "roofing" grade) gives a much finer leafing effect, enabling Tropical Roofing Products to achieve a vastly superior coating. Our use of naturally occurring bituminous resins fortifies the asphalt with unparalleled strength to give it greater resistance to the damaging effects of the elements. #120 Fibered Aluminum Roof Coating meets and exceeds all the requirements of ASTM D-2824-06 Type III and Federal Specification TTC 1079.

**PREPARATION:** Surface must be clean and dry, free of moisture both on and beneath the surface. Sweep roof thoroughly to remove as much dust, dirt and debris as possible. Use wire brush to remove rust and scale from metal. After careful inspection of entire roof, repair all holes, cracks, tears or breaks with reinforcing fabric and #701 Flashing Cement. **ALLOW REPAIRS TO CURE 30 DAYS BEFORE COATING.**

**APPLICATION:** Apply a thin, single coat of #120 over the entire surface with a soft bristle brush, paint roller or heavy-duty spray equipment. Avoid over-application. **DO NOT HEAT CONTAINER. DO NOT THIN.** Stir thoroughly before and during application. Do not work coating excessively during application. Attempt to brush or roll on in one direction.

**COVERAGE:** Apply at the rate of 1 to 1-1/2 gallons per 100 square feet.

**PRECAUTIONS:** Do not heat container or store at temperatures greater than 120°F. **DO NOT APPLY IF THERE IS A THREAT OF RAIN OR DEW WITHIN 24 HOURS.** Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur. This coating is not recommended over PVC sheet roofing, rubber, gravel, shingles of any kind, or old roofs that are too dry and brittle. Applying #120 directly over hot applied asphalt can result in alligatoring.

**DO NOT USE IF RAIN IS IMMINENT - COATING MUST BE DRY BEFORE EXPOSURE TO WATER  
CAUTION - Apply according to ASTM D3805, allow roof to cure thoroughly before coating.**

**MAXIMUM V.O.C = 500 G/L**  
CONSISTENCY — Semi-Mastic  
WEIGHT — 7.8 +/- .3 lbs. per gal  
FLASH POINT (T.C.C.) — 105°F+  
DRY FILM CHARACTERISTICS — Firm, Non-Tacky Bright Aluminum  
DRYING TIME — Average: 1-2 hrs. to touch

**ASTM  
D-2824  
FED SPEC  
TTC 1079**

[www.tropicalroofingproducts.com](http://www.tropicalroofingproducts.com)



FLORIDA  
1904 SW 31st Ave.  
Hallandale, FL 33009  
fax: 954.963.2033  
toll-free: 800.432.2855

CALIFORNIA  
14435 Macaw Street  
La Mirada, CA 90638  
fax: 714.670.1605  
toll-free: 877.827.2622

TEXAS  
1225 Brai Drive, P.O. Box 5335  
Port Arthur, TX 77640  
fax: 409.727.4647  
toll-free: 866.727.0091





# #120 FIBERED ALUMINUM ROOF COATING

**CLEANUP:** Clean tools with mineral spirits or paint thinner.

**CAUTION! COMBUSTIBLE!**

Contains petroleum distillate. Keep away from heat and flame. **USE ONLY WITH ADEQUATE VENTILATION!** Avoid contact with skin and breathing of vapor. **CLOSE AIR INTAKES** on roof until solvents dissipate. **KEEP OUT OF REACH OF CHILDREN.** Close container after each use. Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur. **DO NOT TAKE INTERNALLY!** If swallowed, do not induce vomiting. **CALL PHYSICIAN IMMEDIATELY!** Contains volatile solvents that might contaminate potable water.

**For a totally unsurpassed fibered aluminum coating ask for Tropical's #110 with even 25% more aluminum pigment per gallon.**

[www.tropicalroofingproducts.com](http://www.tropicalroofingproducts.com)



FLORIDA  
1904 SW 31st Ave.  
Hallandale, FL 33009  
fax: 954.963.2033  
toll-free: 800.432.2855

CALIFORNIA  
14435 Macaw Street  
La Mirada, CA 90638  
fax: 714.670.1605  
toll-free: 877.827.2622

TEXAS  
1225 Brai Drive, P.O. Box 5335  
Port Arthur, TX 77640  
fax: 409.727.4647  
toll-free: 866.727.0091

