



#363



FIBERED EMULSION

TROPICAL ASPHALT's #363 Fibered Emulsion is a versatile, protective, fiber reinforced water-based roof and waterproof coating. #363 is a solvent free, all purpose, fibered coating ideal for use as a surface coating for built up roofing, metal, and masonry surfaces, and for pipes and tanks above or below ground level. #363 is made from asphalt emulsified with bentonite clay, water and organic fibers. #363 is cold-applied, corrosion-resistant and waterproof when dry, while also resisting most corrosive fumes and spray. #363 will not run, sag, crack, or "alligator," under the harshest of weather conditions.

PREPARATION: All surfaces must be clean, have proper drainage, and be free from rust, dirt, and all other foreign matter. Remove rust with wire brush. A better bond will result if surface is damp when #363 is applied, but surface must be free of standing water. Clean all cracks, holes and damaged areas, repairing when necessary and allow repairs to thoroughly cure.

APPLICATION: Apply #363 by roofing brush, roller, or spray, evenly covering the surface. Two coats are recommended. Allow to dry completely between coats. Dry time is usually 6-24 hours in dry and hot weather conditions. In cool, damp weather drying will be slower, 2 – 7 days.

COVERAGE: #363 should be applied at a rate of 2 – 3 gallons per 100 square feet, dependent upon roof surface.

PRECAUTION: Do not apply when ambient temperature is below 55°F, or if there is a threat of rain, heavy dew, or temperatures below 40°F within 48 hours. Do not heat container or store at temperatures greater than 120°F. Application over hot applied asphalt may not prevent alligating. This coating is not recommended over gravel, rubber or PVC sheet roofing, or old roofs that are too dry and brittle. When transporting this product, be sure the pail is secured and the lid is tight. Do not allow pail to tumble as this may loosen the lid and allow leakage to occur.

- **DO NOT USE IF RAIN IS IMMINENT.**
- **DO NOT ALLOW #363 TO FREEZE.**
- **COATING MUST BE DRY BEFORE EXPOSURE TO WATER.**

CLEAN UP: Fresh coating can be removed with warm water and soap. If material has started to dry, use mineral spirits or paint thinner.

CAUTION: DO NOT TAKE INTERNALLY! KEEP OUT OF REACH OF CHILDREN. Use protective measures to avoid contact with eyes and skin. If swallowed, CALL PHYSICIAN IMMEDIATELY! In case of eye contact, open eyelids wide and flush immediately with plenty of water for at least 15 minutes. GET MEDICAL ATTENTION! **CAUTION! KEEP OUT OF REACH OF CHILDREN.** Close container after each use. **DO NOT TAKE INTERNALLY! If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY!**

Calif. Prop.65 Chemical Warning (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ) Detectable amounts of some chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm may be found in various Tropical Asphalt petroleum based products and their vapors. Read and follow label directions and information given on Material Safety Data Sheets and use care when handling or using all petroleum products.

MAXIMUM V.O.C = 30 G/L

ASTM D-1227, Type II, Class I

14435 Macaw Street
La Mirada, CA 90638

714-739-1408 * FAX 714-670-1605
Toll Free 1-877-827-2622

1904 S. 31st Avenue
Hallandale, Florida 33009

954-983-3434 ~ FAX: 954-963-2033
Toll Free: 1-800-432-2855

1225 Brai Drive ~ P. O. Box 5335
Port Arthur, Texas 77640

409-727-0091 ~ 409-727-4647 FAX
Toll Free 866-727-0091

www.tropicalasphalt.com