



#4003



FIBERED ROOF

RESATURANT & SEALER

TROPICAL ASPHALT's #4003 is ready to use as it comes from the can. #4003 is a mixture of penetrating solvents, select asphalt, fortifiers, drying agents and hardeners that give this superior product exceptional quality. #4003's strong solvent base enables it to penetrate the old mat, rejuvenating it with fresh oils to keep it from drying out and cracking. The drying agents in #4003 cure the asphalt enough to make the roof accessible without giving up the essential ductility of the coating. #4003 forms a continuous durable waterproof seal that will not crack under the harshest of conditions. #4004 exceeds the requirements for ASTM D-4479.

PREPARATION: All surfaces must be clean, dry, smooth, even and free from all other foreign matter. Raised edges, buckles and blisters should be cut and flattened. Check flashings, drains, edgings, vents, and valleys and repair as needed. Local building codes, roof deck condition, or moisture in old roof may indicate complete removal of an old roof.

APPLICATION: Apply to clean dry surface using stiff, bristle brush, roller or spray equipment. For best results, weather should be at least 65°F, dry and clear, with no threat of rain for 48 hours. Drying time is approximately 48 hours in warm, dry weather.

COVERAGE: Apply at the rate of approximately 35 square feet per gallon, depending on job specifications. Stir coating to uniform consistency before using. Avoid heavy mounds of mass accumulation.

PRECAUTIONS: DO NOT THIN. DO NOT HEAT CONTAINER or store at temperatures greater than 120°F. Be sure lid is tight and pail is secure when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage to occur.

CLEANUP: Clean tools with mineral spirits or paint thinner.

CAUTION! COMBUSTIBLE!

Contains petroleum distillate. Keep away from heat and flame. **USE ONLY WITH ADEQUATE VENTILATION!** Avoid contact with skin and breathing of vapor. **CLOSE AIR INTAKES** on roof until solvents dissipate. **KEEP OUT OF REACH OF CHILDREN.** Close container after each use. **DO NOT TAKE INTERNALLY!** If swallowed, do not induce vomiting. **CALL PHYSICIAN IMMEDIATELY!** Contains volatile solvents that might contaminate potable water.



CONSISTENCY.....	Thick Black Liquid
WEIGHT.....	8.8 lbs. per gal
FLASH POINT (T.C.C.).....	107°F+
DRYING TIME.....	Average: 2 - 5 hrs. to touch



MAXIMUM V.O.C = 300 G/L

14435 Macaw Street
La Mirada, CA 90638
714-739-1408 * FAX 714-670-1605
Toll Free 1-877-827-2622

1904 S. 31st Avenue
Hallandale, Florida 33009
954-983-3434 ~ FAX: 954-963-2033
Toll Free: 1-800-432-2855

1225 Brai Drive ~ P. O. Box 5335
Port Arthur, Texas 77640
409-727-0091 ~ 409-727-4647 FAX
Toll Free 866-727-0091

www.tropicalasphalt.com