



# #410



## QUICK DRY PRIMER

**TROPICAL ASPHALT's # 410 QUICK DRY ASPHALT PRIMER** is an asphalt-based material used as a fast-drying bonding coat and for priming surfaces prior to the application of cold applied and hot mopped asphalt coatings, roof cements, mastics and adhesives. #410 dries fast and is ready to use as it comes from the can.

**PREPARATION:** Surface must be clean and dry, free of moisture both on and beneath the surface. Scrape off gravel to provide a smooth surface. Sweep roof thoroughly to remove as much dust, dirt and debris as possible. Use wire brush to remove rust and scale from metal.

**APPLICATION:** Apply a thin, single coat of #410 over the entire surface with a roofing brush or heavy-duty spray equipment. Brush out any excess immediately after application. Avoid over-application and build-up of surface film. Allow to dry thoroughly before applying adhesives or coatings. Allow sufficient weathering to enhance bonding performance. Store primer in a warm room overnight before using in cold weather. Drying time varies with weather conditions. **DO NOT HEAT CONTAINER. DO NOT THIN.**

**COVERAGE:** Proper application will cover approximately 100-200 square feet per gallon, depending on surface porosity.

**PRECAUTIONS:** Do not heat container or store at temperatures greater than 120°F. Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur. **DO NOT USE** with solvent sensitive insulation, wood shingles or wood flashings. This coating is not recommended over PVC sheet roofing, rubber, gravel, shingles of any kind, or old roofs that are too dry and brittle.

**CLEANUP:** Clean tools with mineral spirits or paint thinner.

**CAUTION! COMBUSTIBLE!**

Contains petroleum distillate. Keep away from heat and flame. **USE ONLY WITH ADEQUATE VENTILATION!** Avoid contact with skin and breathing of vapor. **CLOSE AIR INTAKES** on roof until solvents dissipate. **KEEP OUT OF REACH OF CHILDREN.** Close container after each use. **DO NOT TAKE INTERNALLY!** If swallowed, do not induce vomiting. **CALL PHYSICIAN IMMEDIATELY!** Contains volatile solvents that might contaminate potable water.



**MAXIMUM V.O.C = 350 G/L**



14435 Macaw Street  
La Mirada, CA 90638  
714-739-1408 \* FAX 714-670-1605  
Toll Free 1-877-827-2622

1904 S. 31st Avenue  
Hallandale, Florida 33009  
954-983-3434 ~ FAX: 954-963-2033  
Toll Free: 1-800-432-2855

1225 Brai Drive ~ P. O. Box 5335  
Port Arthur, Texas 77640  
409-727-0091 ~ 409-727-4647 FAX  
Toll Free 866-727-0091