



TROPICAL ASPHALT

#900 WHITE ROOF PAINT

TROPICAL ASPHALT's #900 White Roof Paint is a good quality, polymer latex based roof paint that forms a seamless and durable layer of protection for your roof. #900 White Roof Paint is designed to seal and dramatically reduce the surface temperatures. #900 White Roof Paint is formulated to provide a tough, durable weather resistant coating. #900 White Roof Paint adheres readily to most roofing substrates. #900 White Roof Paint provides a protective and reflective finish that will keep the sun's damaging rays from prematurely aging your roof, while keeping the substrate temperatures substantially lower to alleviate stress on the membrane.

PREPARATION: Surface must be clean and dry, free of moisture both on and beneath the surface. Sweep roof thoroughly to remove as much dust, dirt and debris as possible. Use wire brush to remove rust and scale from metal. After careful inspection of entire roof, repair all holes, cracks, tears or breaks with reinforcing fabric and #950 Eternamastic. #950 Eternamastic repairs can usually be coated within 24-36 hours, if solvent-based roofing cement is used to repair, it must cure for 30 days to avoid any bleed through. Coat newly applied asphalt emulsion as soon as the emulsion can take foot traffic without scuffing or sticking to the surface, normally 1 – 7 days.

APPLICATION: Apply on warm, sunny days, preferably in the morning hours to provide maximum cure time. #900 can be applied to a dry or slightly damp, but not wet, surface. Water must be swept out of all puddles prior to application of #900. Stir #900 thoroughly before application to achieve a uniform consistency. Apply with a heavy-duty paint roller or heavy-duty spray equipment. When applied with roller or brush strokes should be kept in one direction. Apply second coat perpendicular to the first. Allow at least 4 hours between coats and 24-48 hours for full cure, dependent upon weather conditions. Relative humidity will directly affect drying/curing time. Avoid over-application. **DO NOT HEAT CONTAINER. DO NOT THIN.**

PRECAUTIONS: DO NOT APPLY IF TEMPERATURE IS BELOW 55° F or above 110°F. DO NOT APPLY IF THERE IS A THREAT OF RAIN OR DEW WITHIN 48-72 HOURS. Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur. **DO NOT ALLOW PRODUCT TO FREEZE.** Do not heat container or store at temperatures greater than 120°F. This coating is not recommended for areas with inadequate drainage (ponding water), over gravel, over walking decks, polyurethane foam, rubber or PVC sheet roofing, or old roofs that are too brittle and dry. DO NOT APPLY TO FLAT SURFACES WITH POOR DRAINAGE OR WHERE PONDING WATER WILL EXIST.

COVERAGE: Proper application over smooth surface will cover approximately 100 square feet per gallon, per coat, dependent upon roof porosity. Two coats are required, for a minimum total of 2 gallons per 100 square feet.

CLEANUP: Clean tools with mineral spirits or paint thinner, if coating has dried. If coating is still wet, clean up with warm soapy water.

**KEEP OUT OF REACH OF CHILDREN. Close container after each use.
DO NOT TAKE INTERNALLY! If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY!**

V. O. C. = 100 grams/liter

TROPICAL ASPHALT

14435 Macaw Street
La Mirada, CA 90638
714-739-1408 * FAX 714-670-1605
Toll Free 1-877-827-2622

1904 S. 31st Avenue
Hallandale, Florida 33009
954-983-3434 * FAX: 954-963-2033
Toll Free: 1-800-432-2855

1225 Brai Drive ~ P. O. Box 5335
Port Arthur, Texas 77640
409-727-0091~409-727-4647FAX
Toll Free 866-727-0091