



#901



WHITE ELASTOMERIC ROOF COATING



TROPICAL ASPHALT's # 901 White Elastomeric Roof Coating is a good quality, Energy Star® rated, highly reflective elastomeric, polymer latex based roof coating that forms a seamless and flexible layer of protection for your roof. This durable coating is designed to seal and dramatically reduce the surface temperatures. #901 White Elastomeric Roof Coating is formulated to provide a tough, durable weather resistant coating. This flexible, fast drying, elastomeric coating adheres readily to most roofing substrates. #901 White Elastomeric Roof Coating provides a protective and reflective finish that will keep the sun's damaging rays from prematurely aging your roof, while keeping the substrate temperatures substantially lower to alleviate stress on the membrane. The flexibility of #901 gives the coating the ability to expand and contract with the movement on the roof.

PREPARATION: Surface must be clean and dry, free of moisture both on and beneath the surface. Sweep roof thoroughly to remove as much dust, dirt and debris as possible. Use wire brush to remove rust and scale from metal. After careful inspection of entire roof, repair all holes, cracks, tears or breaks with reinforcing fabric and #950 Eternamastic. #950 Eternamastic repairs can usually be coated within 24-36 hours, if solvent-based roofing cement is used to repair, it must cure for 30 days to avoid any bleed through. Coat newly applied asphalt emulsion as soon as the emulsion can take foot traffic without scuffing the surface, normally 1 – 7 days.

APPLICATION: Apply on warm, sunny days, preferably in the morning hours to provide maximum cure time. #901 can be applied to a dry or slightly damp, but not wet, surface. Water must be swept out of all puddles prior to application of #901. Stir #901 thoroughly before application to achieve a uniform consistency. Apply with a heavy-duty paint roller or heavy-duty spray equipment. When applied with roller or brush strokes should be kept in one direction. Apply second coat perpendicular to the first. Allow at least 4 hours between coats and 24-48 hours for full cure, dependent upon weather conditions. Relative humidity will directly affect drying/curing time. Avoid over-application. **DO NOT HEAT CONTAINER. DO NOT THIN.**

14435 Macaw Street
La Mirada, CA 90638
714-739-1408 * FAX 714-670-1605
Toll Free 1-877-827-2622

1904 S. 31st Avenue
Hallandale, Florida 33009
34-983-3434 ~ FAX: 954-963-2033
Toll Free: 1-800-432-2855

1225 Brai Drive ~ P. O. Box 5335
Port Arthur, Texas 77640
409-727-0091 ~ 409-727-4647 FAX
Toll Free 866-727-0091

www.tropicalasphalt.com



#901 WHITE



ELASTOMERIC ROOF COATING



COVERAGE: Proper application over smooth surface will cover approximately 100 square feet per 1 gallons of coating, dependent upon roof porosity. Two coats are required, for a minimum total of 2 gallons per 100 square feet.

PRECAUTIONS: **DO NOT APPLY IF TEMPERATURE IS BELOW 55° F or above 110°F. DO NOT APPLY IF THERE IS A THREAT OF RAIN OR DEW WITHIN 48-72 HOURS.** Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur. ***DO NOT ALLOW PRODUCT TO FREEZE.*** Do not heat container or store at temperatures greater than 120°F. This coating is not recommended for areas with inadequate drainage (ponding water), over gravel, over walking decks, or old roofs that are too brittle and dry. **DO NOT APPLY TO FLAT SURFACES WITH POOR DRAINAGE OR WHERE PONDING WATER WILL EXIST.**

CLEANUP: Clean tools with mineral spirits or paint thinner, if coating has dried. If coating is still wet, clean up with warm soapy water.

CAUTION!

**KEEP OUT OF REACH OF CHILDREN. Close container after each use. DO NOT TAKE INTERNALLY!
If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY!**

MAXIMUM V.O.C = 48 G/L

14435 Macaw Street
La Mirada, CA 90638
714-739-1408 * FAX 714-670-1605
Toll Free 1-877-827-2622

1904 S. 31st Avenue
Hallandale, Florida 33009
954-983-3434 ~ FAX: 954-963-2033
Toll Free: 1-800-432-2855

1225 Brai Drive ~ P. O. Box 5335
Port Arthur, Texas 77640
409-727-0091 ~ 409-727-4647 FAX
Toll Free 866-727-0091

www.tropicalasphalt.com