



#960

ETERNALASTIC METAL PRIMER

TROPICAL ASPHALT's #960 ETERNALASTIC Metal Primer is a water-based product designed for use only on rusted metal surfaces. Where there is spot rust, application should occur to the rusted areas only with a wire brush. If rusting is prevalent throughout the roof surface, this product should be applied with an airless sprayer.

BENEFITS:

Promotes Coating Adhesion, Water Based, Easy Application, Environmentally Friendly

COVERAGE: 1 gallon per 200 square feet.

DRYING TIME: 2 hours dependant on temperature and humidity.

STORAGE: In a clean, warm and well-ventilated area. Storage area temperature must be above 45°F.

PRECAUTIONS: DO NOT APPLY IF TEMPERATURE IS BELOW 45° F or above 120°F. DO NOT APPLY IF THERE IS A THREAT OF RAIN OR DEW WITHIN 48-72 HOURS. Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur. **DO NOT ALLOW PRODUCT TO FREEZE.** Do not heat container or store at temperatures greater than 120°F.

CLEANUP: Clean tools with mineral spirits or paint thinner, if primer has dried. If primer is still wet, clean up with warm soapy water.

CAUTION!

KEEP OUT OF REACH OF CHILDREN. Close container after each use. DO NOT TAKE INTERNALLY!
If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY!

PHYSICAL PROPERTIES

Liquid Appearance: White
Percent Solids, Weight: 47.0%
Viscosity (Stormer): 80 - 90 KU

Dry Appearance: White
Application: Brush, Roller or Sprayer
Shelf Life: 12 months (at recommended conditions)

MAXIMUM V.O.C = 207 G/L

14435 Macaw Street
La Mirada, CA 90638
714-739-1408 * FAX 714-670-1605
Toll Free 1-877-827-2622

1904 S. 31st Avenue
Hallandale, Florida 33009
354-983-3434 ~ FAX: 954-963-2033
Toll Free: 1-800-432-2855

1225 Brai Drive ~ P. O. Box 5335
Port Arthur, Texas 77640
409-727-0091 ~ 409-727-4647 FAX
Toll Free 866-727-0091

www.tropicalasphalt.com